SUMMIT

SBC682NKPNR



33.63" x 23.75" x 24.75" (H x W x D)

24" wide, built-in kegerator, approved for commercial, residential, indoor, and outdoor use, with a panel-ready door and stainless steel cabinet

Highlights:

ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings

Meets residential guidelines for home wet bars and similar spaces

Designed for built-in installation under the counter

Product Features:

Large capacity kegerator	5.6 cu.ft. interior can accept a full half barrel keg, two slim quarter kegs, or up to three sixth barrel or Cornelius style kegs; compatible with beer, wine, coffee, or nitro coffee tap systems	
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Weatherproof design	Solid 304 grade stainless steel construction allows placement in the outdoors	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Panel-ready door	Extended hinging allows you to install your own panel overlay on the door, creating a custom look to complement or blend into your own cabinetry (panel size: 29 3/4" H x 23 5/16" W at a 3/4" thickness)	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Tap cool system	Keeps cold air flowing to the tower for consistently cold beer	
Stainless steel floor cover	Interior includes steel cover to protect the floor when loading kegs	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 \checkmark



SUMMIT

SBC682NKPNR Specifications:

Overview	
Nominal Width	24.0" (61 cm)
Nominal Depth	25.0" (64 cm)
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.63" (85 cm)
Width	23.75" (60 cm)
Depth	24.75" (63 cm)
Depth with door at 90°	46.75" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Stainless Stee
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	305.0kWh/yea
Amps	1.25
Voltage/Frequency	115 V AC/60 Hz
Weight	120.0 lbs. (54 kg
Parts & Labor Warranty	1 Yea
Compressor Warranty	5 Years
UPC	761101087450
Kegerator	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Shelf Type	Chrome
Shelf Qty	2
Thermostat Type	Digita
Fan Type	Interio
Refrigerant	R600a
Refrigerant Amount	1.06 oz
High Side PSI	150.0
Low Side PSI	50.0
Level Legs Qty	4



