



# SBC682PNRWKDTWIN



33.63" x 23.75" x 24.75" (H x W x D)

24" wide built-in indoor/outdoor dual tap wine kegerator with panel-ready door, stainless steel exterior, and complete commercial grade wine tap kit

### Highlights:

Customizable door accepts full overlay panels for a seamless look that can blend into cabinetry

Commercially approved to NSF-7 standards

Complete dual tap wine dispensing kit includes tank for nitrogen/CO2 mix, regulator, and all the hardware needed to pour the perfect glass

### Product Features:

Large capacity wine kegerator	5.6 cu.ft. interior can accept a full half barrel or quarter keg, or up to three sixth barrels or Cornelius style kegs
Commercially approved	ETL-S listed to NSF-7 standards and meets UL-471 for use in commercial settings
Panel-ready door	Extended hinging allows you to install your own panel overlay on the door, creating a custom look to complement or blend into your own cabinetry (panel size: 29 3/4" H x 23 5/16" W at a 3/4" thickness)
Weatherproof design	Solid 304 grade stainless steel construction allows placement in the outdoors
Built-in capable	Front-breathing design allows fully recessed installation under counters
Complete dual tap kit	Ships with a complete twin tap wine tap kit that includes a dispenser tower, regulator, and all the connection equipment you need to serve from a 1/6 wine keg or disposable wine keg
Nitrogen/CO2 tank included	Canister is best suited for a 75% nitrogen/25% CO2 mixture
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized wine kegs
Automatic defrost	Reduced user maintenance with auto defrost operation



## SBC682PNRWKDTWIN Specifications:

Overview	
Nominal Width	24.0" (61 cm)
Nominal Depth	25.0" (64 cm)
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.63" (85 cm)
Width	23.75" (60 cm)
Depth	24.75" (63 cm)
Depth with door at 90°	46.75" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	305.0kWh/year
Amps	1.25
Voltage/Frequency	115 V AC/60 Hz
Weight	120.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101087511
Kegeerator	
Door Swing	RHD
Reversible	Reversible w/ Optional Hinge
Tap Kit	Yes
Height with Tap	51.5" (131 cm)
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Chrome
Shelf Qty	2
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant	R600a
Refrigerant Amount	1.06 oz.
High Side PSI	150.0

Low Side PSI	50.0
Inter Height	26.75" (68 cm)
Interior Width	20.0" (51 cm)
Interior Depth	19.0" (48 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	34°F to 68°F (1°C to 20°C)
Sound Level	34.0 db

