# 24" (61 cm) Range Hood


#### PRODUCT MODEL NUMBERS

WVU37UC4F

## **ELECTRICAL REQUIREMENTS**


A 120-volt, 60 Hz., AC-only, 15-amp, fused electrical circuit is required.

## PRODUCT DIMENSIONS



- A. 8<sup>25</sup>/<sub>64</sub>" (21.3 cm)
- B. Centerline
- C. 1" (2.54 cm)
- D. 831/32" (22.8 cm)
- E. 19<sup>11</sup>/<sub>16</sub>" (50 cm)
- F. 11/2" (3.8 cm)
- G. 24" (61 cm)
- H. 55/64" (2.2 cm)
- I. 6<sup>19</sup>/<sub>54</sub>" (16 cm)
- J. 2" (5 cm)

#### **INSTALLATION CLEARANCES**



- A. 18" (45.7 cm) min. clearance upper cabinet to countertop
- B. 24" (61.0 cm) minimum bottom of range hood to cooking surface
- C. 24" (61 cm) min. cabinet opening width
- D. 12" (30.5 cm) minimum cabinet depth
- E. 36" (91.4 cm) base cabinet height

#### **VENTING REQUIREMENTS**

- This range hood is factory set to exhaust the air to the outside through the wall or the roof. A non-vented (recirculating) installation will require a Charcoal Filter Kit. See the "Accessories" section for ordering information.
- Vent system must terminate to the outdoors, except for nonvented (recirculating) installations.
- Do not terminate the vent system in an attic or other enclosed area.
- Do not use a 4" (10.2 cm) laundry-type wall cap.
- Use a 7" (17.8 cm) round metal vent or a 3¼" x 10" (8.3 cm x 25.4 cm) rectangular metal vent, depending on your installation requirements. Rigid metal vent is recommended. Plastic or metal foil vent is not recommended.
- The length of vent system and number of elbows should be kept to a minimum to provide efficient performance.


#### For the most efficient and quiet operation:

- Use no more than three 90° elbows.
- Make sure there is a minimum of 24" (61 cm) of straight vent between the elbows if more than 1 elbow is used.
- Do not install 2 elbows together.
- Use clamps or duct tape to seal all joints in the vent system.
- The vent system must have a damper. If roof or wall cap has a damper, do not use damper supplied with the range hood.
- Use caulking to seal exterior wall or roof opening around the cap.

#### **VENTING METHODS**

Vent system can terminate either through the roof or wall. Use  $3\frac{1}{4}$ " x 10" (8.3 cm x 25.4 cm) rectangular with a maximum vent length of 35 ft (10.7 m) or 7" (17.8 cm) or larger round vent with a maximum length of 50 ft (15.2 m) for vent system.

**NOTE:** Flexible vent is not recommended. Flexible vent creates both back pressure and air turbulence that greatly reduce performance.



- A. 7" (17.8 cm) round vent through roof or 31/4" x 10" (8.3 cm x 25.4 cm) rectangular vent through the roof or wall (purchased separately)
- B. Roof/Wall cap with damper (purchased separately)
- C. 24" (61.0 cm) min. above the cooking surface
- D. Charcoal Filter Kit (purchased separately)
- E. Recirculating grid


## **CALCULATING VENT SYSTEM LENGTH**

To calculate the length of the system you need, add the equivalent feet (meters) for each vent piece used in the system.

# 7" (17.8 cm) Round Vent System

Vent Piece	Round	
45° elbow	2.5 ft (0.8 m)	D
90° elbow	5.0 ft (1.5 m)	
7" (17.8 cm) wall cap	0.0 ft (0.0 m)	
31/4" x 10" (8.3 cm x 25.4 cm) to 7" (17.8 cm)	4.5 ft (1.4 m)	
3½" x 10" (8.3 cm x 25.4 cm) to 7" (17.8 cm) 90° elbow	5.0 ft (1.5 m)	

## **Example vent system**




Maximum Recommended Length	= 50 ft (15.2 m)
1 - 90° elbow	= 5.0 ft (1.5 m)
1 - wall cap	= 0.0 ft (0.0 m)
8 ft (2.4 m) straight	= 8.0 ft (2.4 m)
Length of 7" (17.8 cm) system	= 13.0 ft (3.9 m)

# 31/4" x 10" (8.3 cm x 25.4 cm) Vent System

Vent Piece		
3½" x 10" (8.3 cm x 25.4 cm) 90° elbow	5.0 ft (1.5 m)	
3½" x 10" (8.3 cm x 25.4 cm) flat elbow	12.0 ft (3.7 m)	
31/4" x 10" (8.3 cm x 25.4 cm) wall cap	0.0 ft (0.0 m)	

# **Example vent system**



Maximum Recommended Length	= 35 ft (10.7 m)
1 - 90° elbow	= 5.0 ft (1.5 m)
8 ft (2.4 m) straight	= 8.0 ft (2.4 m)
1 - wall cap	= 0.0 ft (0.0 m)
Length of 31/4" x 10" (8.3 cm x 25.4 cm) system	= 13.0 ft (3.9 m)